



THE FUTURE OF BUSINESS COMMUNICATION, DELIVERED TODAY

MOTOTRBO™ DIGITAL TWO-WAY MOBILE RADIOS

Make technology more productive and personal. You asked for a forward-thinking way to connect your people to their work, wherever they go. An innovative business tool that increases their efficiency while lowering your costs. Versatile and powerful, MOTOTRBO combines the best of two-way radio functionality with the latest digital technology. It integrates voice and data seamlessly, offers enhanced features that are easy to use and delivers increased capacity to meet your communication needs from the field to the factory floor. With exceptional voice quality and long battery life, MOTOTRBO keeps your work teams connected when communication is a must.

HIGH-POWERED PERFORMANCE

Because MOTOTRBO uses TDMA digital technology, it delivers integrated voice and data, twice the calling capacity plus clearer voice communications. In fact, the leading-edge IMPRES™ technology in our audio accessories also ensures clearer audio delivery.

INDUSTRY-LEADING APPLICATIONS

Motorola's Application Developer Program offers customized data applications so you can adapt your radios to your unique business needs. Because we've created the largest developer program in the industry, we can provide nimble applications that address your challenges and answer your objectives – from work order ticket management to network management, email gateways to location tracking, dispatch consoles to telephony integration, and beyond.

Whether you want to send text messages or track work order information, pinpoint work crew locations with integrated GPS or manage your fleet from a central dispatch location, MOTOTRBO paves the way – with customizable data applications on one convenient device.

ADDED FUNCTIONALITY

MOTOTRBO offers added functionality, including dispatch capability with the MIP 5000 VoIP console, enhanced call signaling, basic and enhanced privacy-scrambling, option board expandability and compatibility with SCADA solutions for utility and public service monitoring and alarms. Plus digital telephone interconnect capability to enable communication between radios and landline or mobile phones as well as a transmit interrupt suite – with voice interrupt, emergency voice interrupt or data over voice interrupt – to prioritize critical communication the moment you need it.

EXPANDED CAPACITY AND COVERAGE

Your workforce is hard at work every day – picking up loads, making road repairs, providing security, responding to guest requests or restoring power after a storm. That’s why you need the proven performance of MOTOTRBO radio systems for non-stop communication no matter the size of your work force, no matter where they go.

MOTOTRBO’s IP Site Connect dramatically improves customer service and productivity by using the Internet to extend coverage to users anywhere in the world. Our scalable, single-site Capacity Plus solution expands capacity

to over 1,000 users without adding new frequencies. Connect Plus multi-site digital trunking enables you to accommodate the high volume, wide area communication your business requires. Whether you need coverage at a single site or across multiple sites, MOTOTRBO can be scaled to meet your needs.

MIGRATE AT YOUR OWN PACE

Keeping operations running smoothly during a change in communication systems is vital to your business. It’s easy to migrate to digital with MOTOTRBO because radios operate in analog and digital mode while the dynamic mixed mode repeater functionality streamlines automatic switching between analog and digital calls. So you can begin using MOTOTRBO radios and repeaters on your existing analog system, and when your time and budget allow you can begin migrating to digital at your own pace.

RELIABLE DURABILITY

MOTOTRBO mobile radios are backed by a two-year Standard Warranty, one-year Repair Service Advantage (US)/Extended Warranty (Canada) and minimum 1-year warranty for accessories.



XPR™ 4550 / XPR 4580
Display Mobile Radios

XPR 4350 / XPR 4380
Numeric Display Mobile Radios

MOTOTRBO™ XPR™ 4550/XPR 4350 MOBILE RADIOS

GENERAL SPECIFICATIONS

	DISPLAY XPR 4550			NUMERIC DISPLAY XPR 4350		
	VHF	UHF Band I	UHF Band II	VHF	UHF Band I	UHF Band II
Channel Capacity	Up to 1,000			32		
Typical RF Output						
Low Power	1-25 W	1-25 W	—	1-25 W	1-25 W	—
High Power	25-45 W	25-40 W	1-40 W	25-45 W	25-40 W	1-40 W
Frequency	136-174 MHz	403-470 MHz	450-512 MHz	136-174 MHz	403-470 MHz	450-512 MHz
Dimensions	2.01 in H x 6.89 in W x 8.11 in L (51 mm H x 175 mm W x 206 mm L)			2.01 in H x 6.89 in W x 8.11 in L (51 mm H x 175 mm W x 206 mm L)		
Weight	4.0 lbs (1.8 kg)			4.0 lbs (1.8 kg)		
Current Drain:						
Standby	0.81 A max	0.81 A max	0.81 A max	0.81 A max	0.81 A max	0.81 A max
Rx @ Rated Audio	2 A max	2 A max	2 A max	2 A max	2 A max	2 A max
Transmit	1-25 W: 11.0 A max 25-45 W: 14.5 A max	1-25 W: 11.0 A max 25-40 W: 14.5 A max	1-40 W: 14.5 A max (11.0 A max < 25 W)	1-25 W: 11.0 A max 25-45 W: 14.5 A max	1-25 W: 11.0 A max 25-40 W: 14.5 A max	1-40 W: 14.5 A max (11.0 A max < 25 W)
FCC Description	1-25 W: ABZ99FT3083 25-45 W: ABZ99FT3082	1-25 W: ABZ99FT4081 25-40 W: ABZ99FT4080	1-40 W: ABZ99FT4083	1-25 W: ABZ99FT3083 25-45 W: ABZ99FT3082	1-25 W: ABZ99FT4081 25-40 W: ABZ99FT4080	1-40 W: ABZ99FT4083
IC Description	1-25 W: 109AB-99FT3083 25-45 W: 109AB-99FT3082	1-25 W: 109AB-99FT4081 25-40 W: 109AB-99FT4080	1-40 W: 109AB-99FT40830	1-25 W: 109AB-99FT3083 25-45 W: 109AB-99FT3082	1-25 W: 109AB-99FT4081 25-40 W: 109AB-99FT4080	1-40 W: 109AB-99FT4083

RECEIVER: DISPLAY XPR 4550 & NUMERIC DISPLAY XPR 4350

GPS: DISPLAY XPR 4550 & NUMERIC DISPLAY XPR 4350

Frequencies	136-174 MHz	403-470 MHz	450-512 MHz	Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)		
Channel Spacing	12.5 kHz / 25 kHz*			TFFF (Time To First Fix) Cold Start	< 1 minute	
Frequency Stability (-30° C, +60° C, +25° C)	+/- 0.5 ppm			TFFF (Time To First Fix) Hot Start	< 10 seconds	
Analog Sensitivity (12dB SINAD)	0.3 uV 0.22 uV (typical)			Horizontal Accuracy	< 10 meters	
Digital Sensitivity	5% BER: 0.3 uV			MILITARY STANDARDS: DISPLAY XPR 4550 & NUMERIC DISPLAY XPR 4350		
Intermodulation (TIA603C)	78 dB	75 dB		810E		810F
Adjacent Channel Selectivity				Applicable MIL-STD	Methods	Procedures
TIA603	65 dB @ 12.5 kHz, 80 dB @ 25 kHz*	65 dB @ 12.5 kHz, 75 dB @ 25 kHz*		Low Pressure	500.3	II
TIA603C	50 dB @ 12.5 kHz, 80 dB @ 25 kHz*	50 dB @ 12.5 kHz, 75 dB @ 25 kHz*		High Temperature	501.3	I/A, II/A1
Spurious Rejection (TIA603C)	80 dB	75 dB		Low Temperature	502.3	I/C3, II/C1
Rated Audio	3 W (Internal)			Temperature Shock	503.3	I/A1C3
	7.5 W (External - 8 ohms)			Solar Radiation	505.3	I
	13 W (External - 4 ohms)			Rain	506.3	I, II
Audio Distortion @ Rated Audio	3% (typical)			Humidity	507.3	II
Hum and Noise	-40 dB @ 12.5 kHz			Salt Fog	509.3	I
	-45 dB @ 25 kHz*			Dust	510.3	I
Audio Response	TIA603C			Vibration	514.4	I/10, II/3
Conducted Spurious Emission (TIA603C)	-57 dBm			Shock	516.4	I, IV

TRANSMITTER: DISPLAY XPR 4550 & NUMERIC DISPLAY XPR 4350

ENVIRONMENTAL SPECIFICATIONS: DISPLAY XPR 4550 & NUMERIC DISPLAY XPR 4350

Frequencies	136-174 MHz	403-470 MHz	450-512 MHz	Operating Temperature	-30° C / +60° C
Channel Spacing	12.5 kHz / 25 kHz*			Storage Temperature	-40° C / +85° C
Frequency Stability (-30° C, +60° C, +25° C Ref.)	+/- 0.5 ppm			Thermal Shock	Per MIL-STD
Low Power Output	1-25 W	1-25 W	—	Humidity	Per MIL-STD
High Power Output	25-45 W	25-40 W	1-40 W	ESD	IEC-801-2KV
Modulation Limiting	+/- 2.5 kHz @ 12.5 kHz +/- 5.0 kHz @ 25 kHz*			Dust and Water Intrusion	IEC 60529 - IP54
FM Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz*			Packaging Test	MIL-STD 810D and E
Conducted / Radiated Emission	-36 dBm < 1 GHz -30 dBm > 1 GHz				
Adjacent Channel Power	60 dB @ 12.5 kHz 70 dB @ 25 kHz*				
Audio Response	TIA603C				
Audio Distortion	3%				
FM Modulation	12.5 kHz: 11K0F3E 25 kHz*: 16K0F3E				
4FSK Digital Modulation	12.5 kHz Data Only: 7K60FXD 12.5 kHz Data & Voice: 7K60FXE				
Digital Vocoder Type	AMBE +2™				
Digital Protocol	ETSI TS 102 361-1, -2, -3				

*25 kHz will not be available on new equipment in the U.S. after 1/1/2013.
Specifications subject to change without notice. All specifications shown are typical.
Radio meets applicable regulatory requirements. Version 9 03/10

GENERAL SPECIFICATIONS

	DISPLAY XPR 4580	NUMERIC DISPLAY XPR 4380	GPS	
Channel Capacity	Up to 1,000	Up to 32	Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)	
Typical RF Output	806-870 MHz 10-35 W 896-941 MHz* 10-30 W	806-870 MHz 10-35 W 896-941 MHz* 10-30 W	TTF (Time To First Fix) Cold Start	< 1 minute
Frequency Band	800 and 900 MHz	800 and 900 MHz	TTF (Time To First Fix) Hot Start	< 10 seconds
Dimensions	2.01 in H x 6.89 in W x 8.11 in L (51 mm H x 175 mm W x 206 mm L)	2.01 in H x 6.89 in W x 8.11 in L (51 mm H x 175 mm W x 206 mm L)	Horizontal Accuracy	< 10 meters
Weight	4.0 lbs (1.8 kg)	4.0 lbs (1.8 kg)	MILITARY STANDARDS	
Current Drain:				
Standby	0.81 A max	0.81 A max	Applicable MIL-STD	810E 810F
Rx @ Rated Audio	2 A max	2 A max	Methods	Procedures
Transmit	12.0 A max	12.0 A max	Low Pressure	500.3 II 500.4 II
Power Supply	12 V dc Negative Ground	12 V dc Negative Ground	High Temperature	501.3 I/A, II/A1 501.4 I/Hot, II/Hot
FCC Description	ABZ99FT5010	ABZ99FT5010	Low Temperature	502.3 I/C3, II/C1 502.4 I/C3, II/C1
IC Description	109AB-99FT5010	109AB-99FT5010	Temperature Shock	503.3 I/A1C3 503.4 I
			Solar Radiation	505.3 I 505.4 I
			Rain	506.3 I, II 506.4 I, III

RECEIVER

Frequencies	800 MHz: 854-866 MHz and 869-870 MHz 900 MHz: 935-941 MHz	Humidity	507.3 II 507.4 —
Channel Spacing	800 MHz: 12.5 and 25 kHz / 900 MHz: 12.5 kHz	Salt Fog	509.3 I 509.4 I
Frequency Stability (-30° C, +60° C, +25° C)	+/- 0.5 ppm	Dust	510.3 I 510.4 I
Analog Sensitivity (12dB SINAD)	0.22 uV	Vibration	514.4 I/10, II/3 514.5 I/24
Digital Sensitivity	5% BER: 0.28 uV	Shock	516.4 I, IV 516.5 I, IV
Intermodulation (TIA603C)	78 dB	ENVIRONMENTAL SPECIFICATIONS	
Adjacent Channel Selectivity TIA603 TIA603C	65 dB @ 12.5 kHz, 75 dB @ 25 kHz 50 dB @ 12.5 kHz, 75 dB @ 25 kHz	Operating Temperature	-30° C / +60° C
Spurious Rejection (TIA603C)	75 dB	Storage Temperature	-40° C / +85° C
Rated Audio	3 W (Internal)	Thermal Shock	Per MIL-STD
Audio Distortion @ Rated Audio	3% (typical)	Humidity	Per MIL-STD
Hum and Noise	-45 dB @ 12.5 kHz / -45 dB @ 25 kHz	ESD	IEC-801-2KV
Audio Response	TIA603C	Dust and Water Intrusion	IEC 60529 - IP54
Conducted Spurious Emission (TIA603C)	-57 dBm	Packaging Test	MIL-STD 810D and E

TRANSMITTER

		ONLY THE FOLLOWING FREQUENCIES ARE SUPPORTED BY THE XPR 4580 / XPR 4380		
		Band	Receive	Transmit
Frequencies	800 MHz: 809-821 MHz, 824-825 MHz, 854-866 MHz and 869-870 MHz 900 MHz: 896-902 MHz and 935-941 MHz			
Channel Spacing	800 MHz: 12.5 and 25 kHz / 900 MHz: 12.5 kHz	800 MHz	851.0125	806.0125 851.0125
Frequency Stability (-30° C, +60° C, +25° C Ref.)	+/- 0.5 ppm		851.5125	806.5125 851.5125
Low Power Output	10 W		852.0125	807.0125 852.0125
High Power Output	800 MHz: 35W / 900 MHz: 30W		852.5125	807.5125 852.5125
Modulation Limiting	+/- 2.5 kHz @ 12.5 kHz / +/- 5.0 kHz @ 25 kHz		853.0125	808.0125 853.0125
FM Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz		854.000 - 865.9875	809.000 - 820.9875 854.000 - 865.9875
Conducted / Radiated Emission	-36 dBm < 1 GHz / -30 dBm > 1 GHz		866.0125	821.0125 866.0125
Adjacent Channel Power	-50 dB @ 12.5 kHz / -60 dB @ 25 kHz		866.5125	821.5125 866.5125
Audio Response	TIA603C		867.0125	822.0125 867.0125
Audio Distortion	3%		867.5125	822.5125 867.5125
FM Modulation	12.5 kHz: 11K0F3E / 25 kHz: 16K0F3E		868.0125	823.0125 868.0125
4FSK Digital Modulation	12.5 kHz Data Only: 7K60FXD 12.5 kHz Data & Voice: 7K60FXE		869.000 - 870.000	824.000 - 825.000 869.000 - 870.000
Digital Vocoder Type	AMBE +2™	900 MHz	935.000 - 941.000	896.000 - 902.000 935.000 - 941.000
Digital Protocol	ETSI TS 102 361-1, -2, -3			

*For frequencies 901-902, 940-941 MHz, FCC Rule Part 24 limits power to 7W ERP. Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements. Version 1 03/10

For more information on how to make your business more efficient and better connected, visit.

Motorola

205 rue Viger
Montreal, PQ H2Z 1G2
514-394-7497
514-394-7480

CONTACTEZ-NOUS POUR NOTRE PROMOTION SPÉCIAL



Motorola Solutions, Inc. 1301 E. Algonquin Road, Schaumburg, Illinois 60196 U.S.A. motorolasolutions.com

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2011 Motorola Solutions, Inc. All rights reserved. R3-1-2038B

