



THE FUTURE OF BUSINESS COMMUNICATION, DELIVERED TODAY

# MOTOTRBO™ DIGITAL TWO-WAY PORTABLE RADIOS

Make technology more productive and personal. You asked for a forward-thinking way to connect your people to their work, wherever they go. An innovative business tool that increases their efficiency while lowering your costs. Versatile and powerful, MOTOTRBO combines the best of two-way radio functionality with the latest digital technology. It integrates voice and data seamlessly, offers enhanced features that are easy to use and delivers increased capacity to meet your communication needs from the field to the factory floor. With exceptional voice quality and long battery life, MOTOTRBO keeps your work teams connected when communication is a must.

## HIGH-POWERED PERFORMANCE

Because MOTOTRBO uses TDMA digital technology, it delivers integrated voice and data, twice the calling capacity plus clearer voice communications. When it comes to battery performance, MOTOTRBO radios operate 40 percent longer between recharges compared to analog. In fact, the leading-edge IMPRES™ technology in our batteries, chargers and audio accessories also ensures longer talk time and clearer audio.

## INDUSTRY-LEADING APPLICATIONS

Motorola's Application Developer Program offers customized data applications so you can adapt your radios to your unique business needs. Because we've created the largest developer program in the industry, we can provide nimble applications that address your challenges and answer your objectives – from work order ticket management to network management, email gateways to location tracking, dispatch consoles to telephony integration, and beyond.

Whether you want to send text messages or track work order information, pinpoint work crew locations with integrated GPS or manage your fleet from a central dispatch location, MOTOTRBO paves the way – with customizable data applications on one convenient device.



## ADDED FUNCTIONALITY

MOTOTRBO offers added functionality, including dispatch capability with the MIP 5000 VoIP console, enhanced call signaling, basic and enhanced privacy-scrambling, option board expandability and compatibility with SCADA solutions for utility and public service monitoring and alarms. Plus digital telephone interconnect capability to enable communication between radios and landline or mobile phones as well as a transmit interrupt suite – with voice interrupt, emergency voice interrupt or data over voice interrupt – to prioritize critical communication the moment you need it.

## EXPANDED CAPACITY AND COVERAGE

Your workforce is hard at work every day – picking up loads, making road repairs, providing security, responding to guest requests or restoring power after a storm. That’s why you need the proven performance of MOTOTRBO radio systems for non-stop communication no matter the size of your work force, no matter where they go.

MOTOTRBO’s IP Site Connect dramatically improves customer service and productivity by using the Internet to extend coverage to users anywhere in the world. Our scalable, single-site Capacity Plus solution expands capacity to over 1,000 users without adding new frequencies. Connect Plus multi-site digital trunking enables you to

accommodate the high volume, wide area communication your business requires. Whether you need coverage at a single site or across multiple sites, MOTOTRBO can be scaled to meet your needs.

## MIGRATE AT YOUR OWN PACE

Keeping operations running smoothly during a change in communication systems is vital to your business. It’s easy to migrate to digital with MOTOTRBO because radios operate in analog and digital mode while the dynamic mixed mode repeater functionality streamlines automatic switching between analog and digital calls. So you can begin using MOTOTRBO radios and repeaters on your existing analog system, and when your time and budget allow you can begin migrating to digital at your own pace.

## RELIABLE DURABILITY

MOTOTRBO meets the most demanding specs, including IP57 for water submersibility (portables) and U.S. Military 810 C, D, E and F. It’s “intrinsically safe” when purchased and equipped with an FM/CSA battery, for use where flammable gas, vapors or combustible dust may be present. And backed by a two-year Standard Warranty, one-year Repair Service Advantage (US)/Extended Warranty (Canada) and minimum 1-year warranty for accessories.

**XPR 6550 / XPR 6580**  
Display Portable Radios



**XPR 6350 / XPR 6380**  
Non-Display Portable Radios



**PRODUCT SPEC SHEET**

MOTOTRBO™ XPR™ 6550/XPR 6350 PORTABLE RADIOS

**GENERAL SPECIFICATIONS**

	<b>DISPLAY XPR 6550</b>			<b>NON-DISPLAY XPR 6350</b>		
	<b>VHF</b>	<b>UHF Band I</b>	<b>UHF Band II</b>	<b>VHF</b>	<b>UHF Band I</b>	<b>UHF Band II</b>
Channel Capacity	Up to 1,000			32		
Frequency	136-174 MHz	403-470 MHz	450-512 MHz	136-174 MHz	403-470 MHz	450-512 MHz
Dimensions	5.18 in H x 2.5 in W x 1.39 in L (131.5 mm H x 63.5 mm W x 35.2 mm L)			5.18 in H x 2.5 in W x 1.39 in L (131.5 mm H x 63.5 mm W x 35.2 mm L)		
Weight (with IMPRES Li-Ion 1500 mAh Battery) (with IMPRES Li-Ion 1400 mAh FM Battery) (with IMPRES Li-Ion 2150 mAh Battery) (with NiMH 1300 mAh Battery)	12.7 oz (360 g) 13 oz (370 g) 13.17 oz (375 g) 15.2 oz (430 g)			11.63 oz (330 g) 11.98 oz (340 g) 12.12 oz (345 g) 14.09 oz (400 g)		
Power Supply	7.5 V nominal			7.5 V nominal		
FCC Description	AZ489FT3815	AZ489FT4876	AZ489FT4884	AZ489FT3815	AZ489FT4876	AZ489FT4884
IC Description	109U-89FT3815	109U-89FT4876	109U-89FT4884	109U-89FT3815	109U-89FT4876	109U-89FT4884
Average battery life at 5/5/90 duty cycle with battery saver enabled in carrier squelch and transmitter in high power.						
IMPRES Li-Ion 1500 mAh Battery	Analog: 9 hrs Digital: 13 hrs			Analog: 9 hrs Digital: 13 hrs		
IMPRES Li-Ion FM 1400 mAh Battery	Analog: 8.5 hrs Digital: 12 hrs			Analog: 8.5 hrs Digital: 12 hrs		
IMPRES Li-Ion 2150 mAh Battery	Analog: 13.5 hrs Digital: 19 hrs			Analog: 13.5 hrs Digital: 19 hrs		
NiMH 1300 mAh Battery	Analog: 8 hrs Digital: 11 hrs			Analog: 8 hrs Digital: 11 hrs		

**RECEIVER: DISPLAY XPR 6550 & NON-DISPLAY XPR 6350**

**GPS: DISPLAY XPR 6550 & NON-DISPLAY XPR 6350**

Frequencies	136-174 MHz	403-470 MHz	450-512 MHz	Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)						
Channel Spacing	12.5 kHz / 25 kHz*			TTF (Time To First Fix) Cold Start	< 2 minutes					
Frequency Stability (-30° C, +60° C, +25° C)	+/- 0.5 ppm			TTF (Time To First Fix) Hot Start	< 10 seconds					
Analog Sensitivity (12dB SINAD)	0.35 uV 0.22 uV (typical)			Horizontal Accuracy	< 10 meters					
Digital Sensitivity	5% BER: 0.3 uV			<b>MILITARY STANDARDS: DISPLAY XPR 6550 &amp; NON-DISPLAY XPR 6350</b>						
Intermodulation (TIA603C)	70 dB									
Adjacent Channel Selectivity				Applicable MIL-STD	Methods		Procedures			
TIA603	60 dB @ 12.5 kHz, 70 dB @ 25 kHz*			Low Pressure	500.3	II		500.4	II	
TIA603C	45 dB @ 12.5 kHz, 70 dB @ 25 kHz*			High Temperature	501.3	I/A, II/A1		501.4	I/Hot, II/Hot	
Spurious Rejection (TIA603C)	70 dB			Low Temperature	502.3	I/C3, II/C1		502.4	I/C3, II/C1	
Rated Audio	500 mW			Temperature Shock	503.3	I/A, 1C3		503.4	I	
Audio Distortion @ Rated Audio	3% (typical)			Solar Radiation	505.3	I		505.4	I	
Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz*			Rain	506.3	I, II		506.4	I, III	
Audio Response	TIA603C			Humidity	507.3	II		507.4	-	
Conducted Spurious Emission (TIA603C)	-57 dBm			Salt Fog	509.3	I		509.4	I	
				Dust	510.3	I		510.4	I	
				Vibration	514.4	I/10, II/3		514.5	I/24	
				Shock	516.4	I, IV		516.5	I, IV	

**TRANSMITTER: DISPLAY XPR 6550 & NON-DISPLAY XPR 6350**

**ENVIRONMENTAL SPECIFICATIONS: DISPLAY XPR 6550 & NON-DISPLAY XPR 6350**

Frequencies	136-174 MHz	403-470 MHz	450-512 MHz				
Channel Spacing	12.5 kHz / 25 kHz*						
Frequency Stability (-30° C, +60° C, +25° C Ref.)	+/- 0.5 ppm			Operating Temperature -30° C / +60° C			
Low Power Output	1 W	1 W		Storage Temperature -40° C / +85° C			
High Power Output	5 W	4 W		Thermal Shock Per MIL-STD			
Modulation Limiting				Humidity Per MIL-STD			
FM Hum and Noise	-40 dB @ 12.5 kHz -45 dB @ 25 kHz*			ESD IEC-801-2KV			
Conducted / Radiated Emission	-36 dBm < 1 GHz -30 dBm > 1 GHz			Dust and Water Intrusion IEC 60529 - IP57			
Adjacent Channel Power	60 dB @ 12.5 kHz 70 dB @ 25 kHz*			Packaging Test MIL-STD 810D and E			
Audio Response	TIA603C			Testing completed using portable radio with attached battery and antenna.			
Audio Distortion	3%			<b>FACTORY MUTUAL APPROVALS: DISPLAY XPR 6550 &amp; NON-DISPLAY XPR 6350</b>			
FM Modulation	12.5 kHz: 11K0F3E 25 kHz*: 16K0F3E			MOTOTRBO XPR Series portable radios have been certified by FM and CSA Approvals in accordance with Canada and U.S. Codes as intrinsically safe for use in Class I, II, III, Division 1, Groups C, D, E, F, G, when properly equipped with a Motorola FM approved battery option. They are also approved for use in Class I, Division 2, Groups A, B, C, D.			

\*25 kHz will not be available on new equipment in the U.S. after 1/1/2013.  
\*\*Radio only, Li-Ion battery -10° C; NiMH battery -20° C.  
Specifications subject to change without notice. All specifications shown are typical.  
Radio meets applicable regulatory requirements. Version 10 07/10





## PRODUCT SPEC SHEET

MOTOTRBO™ XPR™ 6580/XPR 6380 PORTABLE RADIOS

### GENERAL SPECIFICATIONS

	DISPLAY XPR 6580	NON-DISPLAY XPR 6380	MILITARY STANDARDS				
				810E		810F	
Channel Capacity	Up to 1000	Up to 32	Applicable MIL-STD	Methods	Procedures	Methods	Procedures
Frequency Band	800 and 900 MHz	800 and 900 MHz	Low Pressure	500.3	II	500.4	II
Dimensions (HxWxL) with Li-Ion Battery	5.18 in H x 2.5 in W x 1.39 in L (131.5 mm H x 63.5 mm W x 35.2 mm L)	5.18 in H x 2.5 in W x 1.39 in L (131.5 mm H x 63.5 mm W x 35.2 mm L)	High Temperature	501.3	I/A, II/A1	501.4	I/Hot, II/Hot
Weight with IMPRES Li-Ion 2150 mAh Battery	13.17 oz (375 g)	12.12 oz (345 g)	Low Temperature	502.3	I/C3, II/C1	502.4	I/C3, II/C1
Power Supply	7.5 V nominal	7.5 V nominal	Temperature Shock	503.3	I/A, 1C3	503.4	I
FCC Description	ABZ99FT5011	ABZ99FT5011	Solar Radiation	505.3	I	505.4	I
IC Description	109AB-99FT5011	109AB-99FT5011	Rain	506.3	I, II	506.4	I, III
Average battery life at 5/5/90 duty cycle with battery saver enabled in carrier squelch and transmitter in high power.			Humidity	507.3	II	507.4	—
IMPRES Li-Ion 2150 mAh Battery	Analog: 13 hrs / Digital: 17 hrs	Analog: 13 hrs / Digital: 17 hrs	Salt Fog	509.3	I	509.4	I
IMPRES Li-Ion 1400 mAh Battery	Analog: 9 hrs / Digital: 12 hrs	Analog: 9 hrs / Digital: 12 hrs	Dust	510.3	I	510.4	I
			Vibration	514.4	I/10, II/3	514.5	I/24

### RECEIVER

Frequencies	800 MHz: 854-866 MHz and 869-870 MHz / 900 MHz: 935-941 MHz	Vibration	516.4	I, IV	516.5	I, IV
Channel Spacing	800 MHz: 12.5 and 25 kHz / 900 MHz: 12.5 kHz	Shock	<b>ENVIRONMENTAL SPECIFICATIONS</b>			
Frequency Stability (-30° C, +60° C, +25° C)	+/- 0.5 ppm	Operating Temperature	-30° C / +60° C			
Analog Sensitivity (12 dB SINAD) Typical	0.25 uV	Operating Temperature (w/ IMPRES Li-Ion battery)	-10° C to +60° C			
Digital Sensitivity	5% BER: 0.3 uV	Storage Temperature	-40° C to +85° C			
Intermodulation (TIA603C)	70 dB	Thermal Shock	Per MIL-STD			
Adjacent Channel Selectivity (TIA603) - 1T	60 dB @ 12.5 kHz / 70 dB @ 25 kHz	Humidity	Per MIL-STD			
Adjacent Channel Selectivity (TIA603C) - 2T	45 dB @ 12.5 kHz / 70 dB @ 25 kHz	ESD	IEC-801-2KV			
Spurious Rejection (TIA603C)	70 dB	Dust and Water Intrusion	IEC 60529 - IP54			
Rated Audio	.5 W	Packaging Test	MIL-STD 810D and E			
Audio Distortion @ Rated Audio	3% (typical)	Testing completed using portable radio with attached battery and antenna.				
Hum and Noise	-40 dB @ 12.5 kHz / -45 dB @ 25 kHz	<b>FACTORY MUTUAL APPROVALS</b>				
Audio Response	TIA603C	MOTOTRBO XPR Series portable radios have been certified by FM and CSA Approvals in accordance with Canada and U.S. Codes as intrinsically safe for use in Class I, II, III, Division 1, Groups C, D, E, F, G, when properly equipped with a Motorola FM approved battery option. They are also approved for use in Class I, Division 2, Groups A, B, C, D.				
Conducted Spurious Emission (ETSI)	-57 dBm	 				

### TRANSMITTER

Frequencies	800 MHz: 809-821 MHz, 824-825 MHz, 854-866 MHz and 869-870 MHz 900 MHz: 896-902 MHz and 935-941 MHz	<b>ONLY THE FOLLOWING FREQUENCIES ARE SUPPORTED BY THE XPR 6580 / XPR 6380</b>				
Channel Spacing	800 MHz: 12.5 and 25 kHz / 900 MHz: 12.5 kHz	<b>Band</b>	<b>Receive</b>	<b>Transmit</b>		
Frequency Stability (-30° C, +60° C)	+/- 0.5 ppm	800 MHz	851.0125	806.0125	851.0125	
Low Power Output	1 W		851.5125	806.5125	851.5125	
High Power Output	2.5 W		852.0125	807.0125	852.0125	
Modulation Limiting	+/- 2.5 kHz @ 12.5 kHz / +/- 5.0 kHz @ 25 kHz		852.5125	807.5125	852.5125	
FM Hum and Noise	-40 dB @ 12.5 kHz / -45 dB @ 25 kHz		853.0125	808.0125	853.0125	
Conducted / Rated Emission (ETSI)	-36 dBm < 1 GHz / -30 dBm > 1 GHz		854.000 - 865.9875	809.000 - 820.9875	854.000 - 865.9875	
Adjacent Channel Power	-60 dB @ 12.5 kHz / -70 dB @ 25 kHz		866.0125	821.0125	866.0125	
Audio Response	TIA603C		866.5125	821.5125	866.5125	
Audio Distortion (per EIA)	3%		867.0125	822.0125	867.0125	
FM Modulation	12.5 kHz: 11K0F3E / 25 kHz: 16K0F3E		867.5125	822.5125	867.5125	
4FSK Digital Modulation	12.5 kHz Data Only: 7K60FXD / 12.5 kHz Data & Voice: 7K60FXE		868.0125	823.0125	868.0125	
Digital Vocoder Type	AMBE +2™		869.000 - 870.000	824.000 - 825.000	869.000 - 870.000	
Digital Protocol	ETSI TS 102 361-1, -2, -3		900 MHz	935.000 - 941.000	896.000 - 902.000	935.000 - 941.000
<b>GPS</b>			Specifications subject to change without notice. All specifications shown are typical. Radio meets applicable regulatory requirements. Version 2 07/10			
Accuracy specs are for long-term tracking (95th percentile values > 5 satellites visible at a nominal -130 dBm signal strength)						
TTF (Time To First Fix) Cold Start	< 2 minutes					
TTF (Time To First Fix) Hot Start	< 10 seconds					
Horizontal Accuracy	< 10 meters					

For more information on how to make your business more efficient and better connected, visit [www.motorola.com/mototrbo](http://www.motorola.com/mototrbo).

## Motorola

205 rue Viger  
Montreal, PQ H2Z 1G2  
514-394-7497  
514-394-7480

CONTACTEZ-NOUS POUR NOTRE  
PROMOTION SPÉCIAL



Motorola Solutions, Inc. 1301 E. Algonquin Road, Schaumburg, Illinois 60196  
U.S.A. [motorolasolutions.com](http://motorolasolutions.com)

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2011 Motorola Solutions, Inc. All rights reserved. R3-4-2028B

